



## Specification Sheet

### Rack & Reel Hose 500 psi 1½"

## Product Information

This rubber-lined interior standpipe fire hose is made of 100% polyester jacket. Rack and reel hose is mildew proof and comes pre-folded for customer convenience. It is specifically designed for interior fire fighting purposes and made to be stored in pin racks and fire cabinets. Available with FM and UL approval upon request and comes in 50', 75', and 100' lengths.



Part Number	Service Pressure	Test Pressure	Bowl Size	Weight per 50' Uncoupled	Weight per 50' Coupled
15RRH	250 psi	500 psi	1 <sup>11</sup> / <sub>16</sub> "	4.5 lbs	5.4 lbs

(\* Available with UL Labeling)

## Construction

**The Jacket** is evenly and firmly woven with high strength staple polyester yarn and high strength, low elongation filler polyester yarn. It is seamless and free from physical defects such as lumps, thread knots and irregularities that may compromise the jacket integrity.

**The Lining** is EPDM single ply extrusion and is smooth and free of pits and other imperfections. Tensile strength, liner elongation and adhesion all meet NFPA 1961, FM, and Underwriters Laboratories, Inc. UL-19 standards.

**Testing** - Hydrostatic tests are performed in conformance to ASTM, NFPA, FM, and 1961 and UL-19 testing requirements and standards

**Markings** - Completed assemblies of 50', 75', and 100' lengths are stenciled not less than 4' from each end of the hose using indelible ink. Lettering is at least 1" high stating the name of the manufacturer or coded designation, month and year of manufacture, trade name, country of origin and service test of 250 psi per NFPA 1962.

**UL Labeling** - Superior Fire Hose Inc. has obtained authorization from Underwriters Laboratories Inc. to allow permanent marking of the UL label by stencil in an effort to avoid problems arising from the rubber labels coming off after the hose has been placed in service.

**Warranty** - Upon delivery the hose shall be guaranteed for a period of 10 years against defects in material and workmanship. The warranty will not apply to damage caused from undue exposure to heat, light, chemicals, moisture, and abrasion. The hose must be used for the purpose it was manufactured for to remain under warranty. Defective hose will be replaced free of charge.